



No. of contacts:	A	B	C
14	16.45	12.80	8.60
20	20.00	16.60	9.50
26	24.00	20.40	9.50
36	30.40	26.70	8.60
40	32.95	29.25	9.30
50	39.30	35.60	9.50
68	50.80	46.95	9.30
100	71.05	67.29	9.30

Current rating: 1 AMP.
 Withstanding voltage: 500V AC
 Insulation resistance: 500MΩ Min.
 Contact resistance: 35mΩ max.
 Temperature range: -45°C to +105°C
 ROHS compliant
 Part number:

B03-0XXG11EN-X1

No. of contacts: _____
 14: 14P
 20: 20P
 ?
 100: 100P
 PCB MOUNTING: _____
 A: 1.0mm(for PCB 1.2mm)
 B: 1.4mm(for PCB 1.6mm)

3	Housing	PBT+G.F.30% (UL 94V-0)	Color: black
2	Shell	SPCC	Plating: Ni
1	Terminal	Phosphor bronze	Contact area: Au 5u" Solder area: Sn Under-plating: Ni
Item	Desc.	Material	Remark

△	2020/05/09	Change part number	Jack Chen
△	2015/04/17	Change tolerance	King Zhou
△	2013/10/23	First edition release	King Zhou

QUALITY SYMBOLS
 □: ☒:
 CRITICAL MAJOR
 ▽: ▽:
 ZERO DEFECT S.P.C

Tolerance	
x.	±0.60
.x	±0.40
.xx	±0.25

NAME:	SCSI(HPCN) male clip type for PCB, assembly connector			PART NO.	B03-0XXG11EN-X1		
REV:	D	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.
SCALE:	N:1	DATE:	2013/10/23	Huangmei	Jack Chen		B03-056

lineconn 东莞市林诚塑胶电子有限公司 <http://www.lineconn.com>
 TEL:0769-85181660 85181770

SIDE	DATE	DESCRIPTION	APPROVER
------	------	-------------	----------