



Voltage current rating: 3 AMP.
 Dielectric withstanding voltage: 500V AC
 Contact resistance: 30 mΩ Max.
 Insulation resistance: 500MΩ Min.
 Temperature range: -20℃ to +85℃
 ROHS compliant
 Waterproof rating: IP67

Item	Desc.	Material	Remarks	Part remarks
9	Gland nut	Synthetic resin	Color:black	1pcs
8	Bushing	Synthetic resin	Color:black	1pcs
7	Hood	Synthetic resin	Color:black	1pcs
6	Shell	SPCC	Plating:Ni	1pcs
5	Socket insulator	Synthetic resin	Color:black	1pcs
4	Card	Synthetic resin	Color:blue	2pcs
3	Terminal	Copper alloy	Plating:G/F	8pcs
2	Screw	Steel	Plating:Ni	4pcs
1	Gasket	Synthetic rubber	Color:black	1pcs

SIDE	DATE	DESCRIPTION	APPROVER
8	2021/03/27	Change part number	Shuo Cao
7	2019/10/09	First edition release	King Zhou

QUALITY SYMBOLS		Tolerance	
□ :	☒ :	x.	±0.60
CRITICAL	MAJOR	.x	±0.40
▽ :	▽ :	.xx	±0.25
ZERO DEFECT	S.P.C		

NAME:				PART NO.			
2174053-1,J3/J4 9pin waterproof connector for Mitsubishi servo motor				B01-00911154-01			
REV:	B	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.
SCALE:	N:1	DATE:	2019/10/09	Huangmei	Shuo Cao		B01-029

lineconn 东莞市林诚塑胶电子有限公司 <http://www.lineconn.com>
 TEL:0769-85181660 85181770