



Termination cover  
(1 places)



Wire holder  
(2 places)

Current rating: 1A. 30V AC  
 Insulation resistance: 500MΩ/Min  
 Withstanding voltage: 500V AC/Min  
 Contact resistance: 35mΩ Max  
 Temperature range: -45℃ to +125℃  
 ROHS compliant

Part number:  
 B03-068111E0-X0  
 Wire holder:  
 28AWG or 30AWG wire  
 6: 0.62mm  
 7: 0.75mm  
 9: 0.90mm

4	Cover	PBT+G.F.30% (UL 94V-0)	Color:black
3	Housing	PBT+G.F.30% (UL 94V-0)	Color:black
2	Shell	SPCC	Plating:Ni
1	Terminal	Phosphor bronze	Contact area: Au 5u" Solder area: Sn Under-plating: Ni
Item	Desc.	Material	Remark

△	2021/06/03	Modify incorrect part number	Carl Hu
△	2020/11/13	Change tolerance	Carl Hu
△	2012/08/24	First edition release	King Zhou

QUALITY SYMBOLS		Tolerance	
□:	☒:	x.	±0.60
CRITICAL	MAJOR	.x	±0.40
▽:	▽:	.xx	±0.25
ZERO DEFECT	S.P.C		

NAME:	SCSI(HPCN) 68pin male IDC assembly connector			PART NO.	B03-068111E0-X0		
REV:	E	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.
SCALE:	N:1	DATE:	2012/08/24	Yugong	Carl Hu		B03-075

SIDE	DATE	DESCRIPTION	APPROVER			<b>lineconn 东莞市林诚塑胶电子有限公司</b>		<a href="http://www.lineconn.com">http://www.lineconn.com</a> TEL:0769-85181660 85181770	
------	------	-------------	----------	--	--	-------------------------------	--	---	--

8

7

6

5

4

3

2

1

F

F

E

E

D

D

C

C

B

B

A

A

8

7

6

5

4

3

2

1