







Termination cover
(1 places)



Wire holder
(2 places)

Current rating: 1A. 30V AC
 Insulation resistance: 500MΩ/Min
 Withstanding voltage: 500V AC/Min
 Contact resistance: 35mΩ Max
 Temperature range: -45°C to +125°C
 ROHS compliant

Part number:
 B03-050111E0-X0
 Wire holder:
 28AWG or 30AWG wire
 6: 0.62mm
 7: 0.75mm
 9: 0.90mm

4	Cover	PBT+G.F.30% (UL 94V-0)	Color:black
3	Housing	PBT+G.F.30% (UL 94V-0)	Color:black
2	Shell	SPCC	Plating:Ni
1	Terminal	Phosphor bronze	Contact area: Au 5u" Solder area: Sn Under-plating: Ni
Item	Desc.	Material	Remark

△	2021/06/03	Change part number	Carl Hu
△	2020/11/13	Change tolerance	Carl Hu
△	2010/12/11	First edition release	King Zhou

QUALITY SYMBOLS		Tolerance	
□:	☒:	.x	±0.60
CRITICAL	MAJOR	.x	±0.40
▽:	▽:	.xx	±0.25
ZERO DEFECT	S.P.C		

NAME:	SCSI(HPCN) 50pin male IDC assembly connector			PART NO.	B03-050111E0-X0		
REV:	E	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.
SCALE:	N:1	DATE:	2010/12/11	Yugong	Carl Hu		B03-071