


Contact current voltage: 125V AC
 Δ Current rating: 0.5A
 Insulation resistance: 1000MΩ Min
 Withstanding voltage: 350V AC
 Contact resistance: 70mΩ Max
 Temperature range: -45°C~+105°C
 ROHS compliant

7	Cable clipper	SPCC	Plating: Ni
6	Hood	Zinc alloy	Plating: Ni
5	Screw	Steel	Plating: Ni
4	Cover	LCP+G.F.15% (UL 94V-0)	Color: black
3	Housing	LCP+G.F.15% (UL 94V-0)	Color: black
2	Shell	SPCC	Plating: Ni
1	Terminal	Copper alloy	Contact area: 3u" Solder area: Sn Under-plating: Ni
Item	Desc.	Material	Remarks

A	△	2023/04/09	Changed the contact current voltage	Jack Chen	QUALITY SYMBOLS □: ☒: CRITICAL MAJOR ∇: ∇: ZERO DEFECT S.P.C	Tolerance		NAME: SDR 26P pitch 0.8mm male solder assembly type, zinc alloy hood REV: E UNIT: mm DRW BY CHK BY APP BY DRAWING NO. SCALE: N:1 DATE: 2020/06/05 Huangmei Jack Chen B06-023	PART NO. B06-026311CJ-A1 http://www.lineconn.com TEL: 0769-85181660 85181770
	△	2020/10/23	Added dimension marking	Jack Chen		x: ±0.80			
	△	2020/06/05	First edition release	Jack Chen		.x ±0.50			
	SIDE	DATE	DESCRIPTION	APPROVER		.xx ±0.25			



lineconn 东莞市林诚塑胶电子有限公司
 http://www.lineconn.com
 TEL: 0769-85181660 85181770