


10A,20A,30A



40A

High power terminal:
Voltage current rating: 10~40A
Contact resistance: 2.7mΩ max.

Signal terminal:
Voltage current rating: 5A
Contact resistance: 10mΩ max.

Withstanding voltage: 1000V AC
Insulation resistance: 5000MΩ Min.
Temperature range: -55°C to +125°C
ROHS compliant

Part number:
B08-AW63X1X0-X1

Housing color: _____
1: Black
3: Green
5: White
Terminal plated: _____
4: Au 2u"
5: Au 1u"
Current rating: _____
A: 10A, Dim.A Ø1.7
B: 20A, Dim.A Ø2.8
C: 30A, Dim.A Ø3.2
D: 40A, Dim.A Ø4.6

4	Housing	PBT+30%GF	Color: see part no.
3	Rear shell	Steel	Plating: Sn
2	Front shell	Steel	Plating: Ni
1	Terminal	Brass C3604	Plating: see part no.
Item	Desc.	Material	Remark

△			
△	2023/03/24	Add housing color	Jack Chen
△	2021/05/11	First edition release	Jack Chen

QUALITY SYMBOLS		Tolerance	
□:	☒:	.x	±0.60
CRITICAL	MAJOR	.x	±0.40
▽:	▽:	.xx	±0.25
ZERO DEFECT	S.P.C		

NAME:	13W6 male solder, cup 8.5mm			PART NO.	B08-AW63X1X0-X1		
REV:	B	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.
SCALE:	N:1	DATE:	2021/05/11	Huangmei	Jack Chen		B08-112

SIDE	DATE	DESCRIPTION	APPROVER
8	7	6	5


东莞市林诚塑胶电子有限公司
<http://www.lineconn.com>
 TEL: 0769-85181660 85181770