


10A,20A,30A



40A

Current rating:10/20/30/40 AMP.
 Contact resistance:2.7 milliohms max.
 Withstanding voltage:1000V AC
 Insulation resistance:5000MΩ Min.
 Temperature range:-55℃ to +125℃
 ROHS compliant
 Part No.:

B08-BW73X1X0-X1

Housing color:
 1: Black
 3: Green
 5: White
 Terminal plated:
 4: Au 2u"
 5: Au 1u"
 Current rating:
 A:10A,Dim.A Ø1.7
 B:20A,Dim.A Ø2.8
 C:30A,Dim.A Ø3.2
 D:40A,Dim.A Ø4.6

4	Housing	PBT+30%GF	Color: see part no.
3	Rear shell	SPCC	Plating: Sn
2	Front shell	SPCC	Plating: Ni
1	Terminal	Brass	Terminal plating: see part No.
Item	Desc.	Material	Remarks

QUALITY SYMBOLS

□: CRITICAL
 ▽: ZERO DEFECT
 ☒: MAJOR
 ▽: S.P.C

Tolerance

x. ±0.60
 .x ±0.40
 .xx ±0.25

NAME:

24W7 male solder,cup 8.5mm

PART NO.

B08-BW73X1X0-X1

REV:

A

UNIT:

mm

DRW BY

CHK BY

APP BY

DRAWING NO.

SCALE:

N:1

DATE:

2021/06/14

Qiang Liao

Shuo Cao

B08-097

Lineconn 东莞市林诚塑胶电子有限公司

http://www.lineconn.com

TEL:0769-85181660 85181770

2021/06/14 First edition release Shuo Cao

SIDE DATE DESCRIPTION APPROVER

8

7

6

5

4

3

2

1