


10A,20A,30A



40A

Current rating:10/20/30/40 AMP.  
 Contact resistance:2.7 milliohms max.  
 Withstanding voltage:1000V AC  
 Insulation resistance:5000M $\Omega$  Min.  
 Temperature range:-55 $^{\circ}$ C to +125 $^{\circ}$ C  
 ROHS compliant  
 Part number:

B08-BW74X1X0-X1

Housing color:

1: Black

3: Green

5: White

Terminal plated:

4: Au 2 $\mu$ "

5: Au 1 $\mu$ "

Current rating:

A:10A,Dim.A  $\phi$ 1.7

B:20A,Dim.A  $\phi$ 2.8

C:30A,Dim.A  $\phi$ 3.2

D:40A,Dim.A  $\phi$ 4.6

4	Housing	PBT+30%GF	Color: see part no.
3	Rear shell	SPCC	Plating: Sn
2	Front shell	SPCC	Plating: Ni
1	Terminal	Brass	Terminal plating: see part No.
Item	Desc.	Material	Remarks

$\Delta$	2025/06/03	Change tolerance	Shuo Cao	
$\Delta$	2021/06/14	First edition release	Shuo Cao	
SIDE	DATE	DESCRIPTION	APPROVER	
8	7	6	5	4

QUALITY SYMBOLS		Tolerance	
$\square$ :	$\boxtimes$ :	x.	$\pm 0.60$
CRITICAL	MAJOR	.x	$\pm 0.40$
$\nabla$ :	$\nabla$ :	.xx	$\pm 0.25$
ZERO DEFECT	S.P.C		

NAME:	24W7 female solder,cup 8.5mm			PART NO.	B08-BW74X1X0-X1		
REV:	B	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.
SCALE:	N:1	DATE:	2021/06/14	Qiang Liao	Shuo Cao		B08-098
<b>东莞市林诚塑胶电子有限公司</b>				<a href="http://www.lineconn.com">http://www.lineconn.com</a> TEL:0769-85181660 85181770			
8	7	6	5	4	3	2	1