



13	Nut	PA66	Color: brown
12	Clip	POM	Color: white
11	Sealing gasket	Rubber	Color: black
10	Seal Ring	rubber	
9	Spring	Stainless spring steel	
8	Terminals	Copper alloy	Plating: Au
7	Housing	PPS	Color: black
6	Connection sleeve	Zinc alloy	Plating: Ni
5	O-Ring	rubber	
4	Spring Washer	Stainless spring steel	
3	Crown Spring	Copper	Plating: Ni
2	Connection sleeve	Zinc alloy	Plating: Ni
1	Shell	Zinc alloy	Plating: Ni
Item	Desc.	Material	Remark

Current rating: 10A
 Operating voltage: 125V
 Contact resistance: 6mΩ Max.
 Durability: 1000 cycles
 Temperature range: -25°C to +85°C
 ROHS compliant

				QUALITY SYMBOLS	Tolerance	NAME: LF10WBP-4S female solder zinc alloy hood assembly				PART NO.	B10-0LF10WBP-4S		
				□: CRITICAL	x. ±0.60	REV:	A	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.
				⊕: ZERO DEFECT	.x ±0.40	SCALE:	N:1	DATE:	2024/08/26	Yugong	Carl Hu		B10-197
				▽: S.P.C	.xx ±0.25	 东莞市林诚塑胶电子有限公司				http://www.lineconn.com TEL: 0769-85181660 85181770			
SIDE	DATE	DESCRIPTION	APPROVER										
8	7	6	5	4	3	2	1						

2024/08/26 First edition release
 Carl Hu