



- Notes:
- 1.Electrical test:100% open,short&miss wire test.
 - 2.Conductor resistance:5Ω max.
 - 3.Insulator resistance: 5MΩ min, DC 300V 0.01sec.
 - 4.ROHS compliant
 - 5.Part number description:A09-V6811XXX-S2, XXX: 001=length: 10cm

2	Cable	UL2919 34P*28AWG+AL+braid,PVC jacket, color:black,OD 10.00mm	NA
1	Connector	VHDCI(pitch 0.8mm) 68pin male solder, zinc alloy hood with screw,M2.0	2set
Item	Part name	Description	Qty

				QUALITY SYMBOLS	Tolerance		NAME: VHDCI 68pin male to male cable			PART NO.	A09-V6811XXX-S2				
A	SIDE	DATE	DESCRIPTION	APPROVER	<input type="checkbox"/> : <input checked="" type="checkbox"/> : CRITICAL MAJOR <input checked="" type="checkbox"/> : <input type="checkbox"/> : ZERO DEFECT S.P.C	Length(mm)	Tolerance(mm)	REV:	B	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.
						300~2000	±50	SCALE:	NONE	DATE:	2014/04/19	Yugong	Carl Hu		A09-009
						2001~5000	±100								
						5001~	±150								
								Lineconn 东莞市林诚塑胶电子有限公司			http://www.lineconn.com TEL:0769-85181660 85181770				