



High power terminal:
Voltage current rating: 10~40A
Contact resistance: 2.7mΩ max.

Signal terminal:
Voltage current rating: 5A
Contact resistance: 10mΩ max.

Withstanding voltage: 1000V AC
Insulation resistance: 5000MΩ Min.
Temperature range: -55°C to +125°C
ROHS compliant

Part number:
B08-AW1511XD-X1
Terminal plated: _____
4: Au 2u"
5: Au 1u"
Current rating: _____
A: 10A, Dim. A φ1.70, Dim. B φ2.20
B: 20A, Dim. A φ2.80, Dim. B φ3.30
C: 30A, Dim. A φ3.20, Dim. B φ3.70
D: 40A, Dim. A φ3.70 Dim. B φ4.20

7	Screw	Steel	Palting: Ni
6	Board lock	Copper alloy	Palting: Sn
5	Bracket	Steel	Palting: Ni
4	Housing	PBT+30%GF	Color: black
3	Rear shell	SPCC	Palting: Sn
2	Front shell	SPCC	Palting: Ni
1	Terminal	Copper alloy	Plating: see part no.
Item	Desc.	Material	Remark

A	△			QUALITY SYMBOLS	Tolerance x: ±0.60 .x ±0.40 .xx ±0.25 	NAME:	11W1 male right angle, riveted insert, lock screw			PART NO.	B08-AW1511XD-X1		
	△	2018/05/09	Add terminal plating type	Carl Hu		REV:	B	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.
	△	2017/05/13	First edition release	Jing Li		CRITICAL MAJOR	SCALE:	N:1	DATE:	2017/05/13	Yugong	Carl Hu	B08-043
	SIDE	DATE	DESCRIPTION	APPROVER		ZERO DEFECT S.P.C	东莞市林诚塑胶电子有限公司			http://www.lineconn.com TEL: 0769-85181660 85181770			
	8	7	6	5	4	3	2	1					