

PCB layout

No. of Contact	A	B	C	D
09	16.30	25.00	30.80	11.08
15	24.80	33.30	39.20	19.39
25	38.30	47.04	53.04	33.24
37	54.80	63.50	69.40	49.86

Current rating: 5 AMP.
 Withstanding voltage: 1000V AC
 Insulation resistance: 5000MΩ Min.
 Temperature range: -45°C to +125°C
 ROHS compliant
 Part number:

B05-0XX6X14D-B2

No. of contact:

- 09: 9pin
- 15: 15pin
- 25: 25pin
- 37: 37pin

Housing color:

- 1: black
- 5: white
- 6: blue


Item	Desc.	Material	Remark
8	Riveted insert	Brass	Plating: Sn
7	Bracket	SPCC	Plating: Ni
6	Nut	Steel	Plating: Ni
5	Bracket	PBT+30%GF	Color: black
4	Housing	PBT+30%GF	Color: see part no.
3	Rear shell	SPCC	Plating: Sn
2	Front shell	SPCC	Plating: Ni
1	Terminal	Brass	Terminal finish: see part no.

QUALITY SYMBOLS

- : CRITICAL
- ☒: MAJOR
- ▽: ZERO DEFECT
- ▽: S.P.C

Tolerance

- x. ±0.60
- .x ±0.40
- .xx ±0.25



NAME:	D-SUB machined pin female right angle, 10.4mm, riveted bracket, nut 4.8mm				PART NO.	B05-0XX6X14D-B2			
REV:	B	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.		
SCALE:	N:1	DATE:	2016/10/23	Huangmei	Carl Hu		B05-062		

lineconn 东莞市林诚塑胶电子有限公司 <http://www.lineconn.com>
 TEL: 0769-85181660 85181770

SIDE	DATE	DESCRIPTION	APPROVER
△	2023/04/10	Change size	Carl Hu
△	2016/10/23	First edition release	Jack Chen