



Contact current rating: 1 Amp
 Dielectric withstanding voltage: 500V AC
 Insulation resistance: 500MΩ Min.
 Contact resistance: 35mΩ Max
 Temperature range: -45°C to +105°C
 ROHS compliant
 Part No.:

Solder area: B01-014311X2-01
 3: G/F
 C: Sn

Item	Desc.	Material	Remarks
10	Screw	Steel	Plating: Ni, M2.0
9	Screw	Steel	Plating: Ni
8	Nut	Steel	Plating: Ni
7	Hood	PBT	Color: black
6	Latch	ABS, SUS 304	Color: black
5	Clamp	Steel	Plating: Ni
4	Cover	PBT+30%GF	Color: black
3	Housing	PBT+30%GF	Color: black
2	Shell	SPCC	Plating: Ni
1	Terminal	Copper alloy	Contact area: Au 3u" Solder area: see part no. Under-plating: Ni

A		B		C		D		E		F	
△	2026/04/24	Modify the drawing based on the actual product	Shuo Cao	QUALITY SYMBOLS		Tolerance		NAME: SM(SCSI) 14pin male solder assembly plastic hood with latch		PART NO. B01-014311X2-01	
△	2022/07/13	Added the size of the cable clamp	Shuo Cao	□: □	⊠: ⊠	x. ±0.60	REV: F	UNIT: mm	DRW BY	CHK BY	APP BY
△	2009/06/04	First edition release	King Zhou	CRITICAL MAJOR	▽: ▽	.x ±0.40	SCALE: N:1	DATE: 2009/06/04	Huangmei	Shuo Cao	DRAWING NO. B01-010
SIDE	DATE	DESCRIPTION	APPROVER	ZERO DEFECT	S.P.C	.xx ±0.25	Lineconn 东莞市林诚塑胶电子有限公司		http://www.lineconn.com		
8	7	6	5	4	3	2	TEL: 0769-85181660 85181770		1		