



High power terminal:
Voltage current rating: 10~40A
Contact resistance: 2.7mΩ max.

Signal terminal:
Voltage current rating: 5A
Contact resistance: 10mΩ max.

Withstanding voltage: 1000V AC
Insulation resistance: 5000MΩ Min.
Temperature range: -55°C to +125°C
ROHS compliant

Part number:
B08-AW5511XD-X1
Terminal plated: _____
4: Au 2u"
5: Au 1u"
Current rating: _____
A: 10A, Dim.A ϕ 1.70, Dim.B ϕ 2.20
B: 20A, Dim.A ϕ 2.80, Dim.B ϕ 3.30
C: 30A, Dim.A ϕ 3.20, Dim.B ϕ 3.70
D: 40A, Dim.A ϕ 3.70 Dim.B ϕ 4.20



7	Screw	Steel	Palting: Ni
6	Board lock	Copper alloy	Palting: Sn
5	Bracket	Steel	Palting: Ni
4	Housing	PBT+30%GF	Color: black
3	Rear shell	SPCC	Palting: Sn
2	Front shell	SPCC	Palting: Ni
1	Terminal	Copper alloy	Plating: see part no.
Item	Desc.	Material	Remark

A	△	2021/06/24	Change part number	Carl Hu	QUALITY SYMBOLS □: ☒: CRITICAL MAJOR	Tolerance .x ±0.60 .x ±0.40 .xx ±0.25	NAME: 17W5 male right angle, riveted bracket, lock screw				PART NO.	B08-AW5511XD-X1	
	△	2019/04/10	Add dimension annotations	Jack Chen			REV: D	UNIT: mm	DRW BY	CHK BY	APP BY	DRAWING NO.	B08-049
	△	2018/09/22	First edition release	Jing Li	▽: ▽: ZERO DEFECT S.P.C	SCALE: N:1	DATE: 2018/09/22	Yugong	Carl Hu				
	SIDE	DATE	DESCRIPTION		APPROVER	东莞市林诚塑胶电子有限公司 http://www.lineconn.com TEL: 0769-85181660 85181770							