



PCB layout

Contact current voltage: 125V AC  
 △ Current rating: 0.5A  
 Insulation resistance: 1000MΩ Min  
 Withstanding voltage: 350V AC  
 Contact resistance: 70mΩ Max  
 Temperature range: -45°C~+105°C  
 ROHS compliant

Item	Desc.	Material	Remarks
6	Nut	Copper alloy	Plating: Ni
5	Board lock	Copper alloy	Plating: Ni
4	Cover	PA 9T+33%GF	Color: black
3	Housing	PA 9T+33%GF	Color: black
2	Shell	SPCC	Plating: Ni
1	Terminal	Phosphor bronze	Contact area: Au 30u" Solder area: Sn Under-plating: Ni

△	2026/05/14	Adjust wrong size specifications	Carl Hu
△	2023/04/09	Changed the contact current voltage	Jack Chen
△	2021/04/07	First edition release	Jack Chen
SIDE	DATE	DESCRIPTION	APPROVER
8	7	6	

QUALITY SYMBOLS		Tolerance	
□ :	⊗ :	.x	±0.60
CRITICAL	MAJOR	.x	±0.40
▽ :	▽ :	.xx	±0.25
ZERO DEFECT	S.P.C		

NAME:		SDR pitch 0.8mm female 26pin right angle				PART NO.		B06-026611KA-01	
REV:	C	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.		
SCALE:	N:1	DATE:	2021/04/07	Huangmei	Carl Hu	B06-020			
lineconn		东莞市林诚塑胶电子有限公司				http://www.lineconn.com			
						TEL:0769-85181660 85181770			
8	7	6	5	4	3	2	1		