



Pin assignment

P1	P2
01	01
02	02
03	03
04	04
05	05
06	06
07	07
08	08
09	09
10	10
11	11
12	12
13	13
14	14
15	15
Shell	Shell

Current rating: 3A
 Dielectric strength: 1000V for one minute
 Insulator resistance:
 1000megohms min at 500V DC
 Temperature: -45°C~105°C
 Laber: Yellow color with black character
 ROHS compliant

Item	Desc.	Material	Remark
5	Screw	Steel	Plating: Ni
4	connecting	SPCC	Plating: Ni
3	Housing	PBT+G.F.30% (UL 94V-0)	Color: blue
2	Sheel	SPCC	Plating: Ni
1	Terminal	Copper alloy	Contact area: G/F Solder area: Sn Under-plating: Ni

△	2021/05/29	Change part number	Carl Hu
△	2015/04/22	Add pin digit labeling	Jack Chen
△	2014/07/09	First edition release	Jack Chen
SIDE	DATE	DESCRIPTION	APPROVER
8	7	6	5

QUALITY SYMBOLS		Tolerance	
□:	☒:	.x	±0.60
CRITICAL	MAJOR	.x	±0.40
▽:	▽:	.xx	±0.25
ZERO DEFECT	S.P.C		

NAME:		PART NO.		
MINI GENDER CHANGER D-SUB 15pin male to male adaptor		C05-015161AD-01		
REV:	UNIT:	DRW BY	CHK BY	DRAWING NO.
D	mm	Huangmei	Carl Hu	C15-007
SCALE:	DATE:			
N:1	2014/07/09			
			http://www.lineconn.com TEL:0769-85181660 85181770	

东莞市林诚塑胶电子有限公司