



Pin assignment

P1	P2
01	01
02	02
03	03
04	04
05	05
06	06
07	07
08	08
09	09
10	10
11	11
12	12
13	13
14	14
15	15
Shell	Shell

Current rating: 3A  
 Withstanding voltage: 500V AC  
 Contact resistance: 35mΩ max.  
 Insulation resistance: 500MΩ Min.  
 Temperature range: -45°C to +105°C  
 Label: yellow color with black character  
 ROHS compliant

Item	Desc.	Material	Remark
5	Screw&Nut	Steel	Plating: Ni
4	connecting	SPCC	Plating: Ni
3	Housing	PBT+G.F.30% (UL 94V-0)	Color: blue
2	Sheel	SPCC	Plating: Ni
1	Terminal	Copper alloy	Contact area: G/F Solder area: Sn Under-plating: Ni

△			
△			
△	2019/03/13	First edition release	Carl Hu
SIDE	DATE	DESCRIPTION	APPROVER
8	7	6	5

QUALITY SYMBOLS		Tolerance	
□ :	☒ :	x.	±0.60
CRITICAL	MAJOR	.x	±0.40
▽ :	▽ :	.xx	±0.25
ZERO DEFECT	S.P.C		

NAME:	MINI GENDER CHANGER HD.D-SUB 15pin female to female adaptor			PART NO.	C04-015261AD-01		
REV:	A	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.
SCALE:	N:1	DATE:	2019/03/13	Huangmei	Carl Hu		C04-005
				<a href="http://www.lineconn.com">http://www.lineconn.com</a> TEL: 0769-85181660 85181770			

东莞市林诚塑胶电子有限公司  
<http://www.lineconn.com>  
 TEL: 0769-85181660 85181770