

High frequency contact characteristic
 impedance: 50 ohms
 signal contact current rating: 5A
 Withstanding voltage: 300V
 Insulation resistance: 2000MΩ Min.
 Temperature range: -55°C to +125°C
 ROHS compliant


4	Housing	PBT(UL94V-0)	Color: black
3	Rear shell	SPCC	Plating: Sn
2	Front shell	SPCC	Plating: Ni
1	Terminal	Brass	Terminal finish: Full Au 1u"
Item	Desc.	Material	Remark

QUALITY SYMBOLS

□: ☒: CRITICAL MAJOR
 ▽: ▽: ZERO DEFECT S.P.C

Tolerance

.x ±0.60
 .x ±0.40
 .xx ±0.25



NAME:	7W2 female coaxial connector,solder			PART NO.	B08-7W2H1150-02		
REV:	A	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.
SCALE:	N:1	DATE:	2025/06/26	Huangmei	Carl Hu		B08-154

lineconn 东莞市林诚塑胶电子有限公司

http://www.lineconn.com
 TEL:0769-85181660 85181770

△	2025/06/26	First edition release	2025/06/26
SIDE	DATE	DESCRIPTION	APPROVER
8	7	6	5

