



Current rating: 5A  
 Withstanding voltage: 500V AC  
 Insulation resistance: >1000 mΩ/Min  
 Contact resistance: 30mΩ/Max  
 Operation temperature: -55°C~+125°C  
 ROHS compliant  
 Part number:

B17-0144X1A0-M6

Housing color: \_\_\_\_\_  
 1: Black  
 6: Blue

3	Housing	PBT+G.F.30%	Color: see part no.
2	Shell	SPCC	Plating: Ni
1	Terminal	Phosphor copper	Contact area: G/F Solder area: Sn Under-plating: Ni
Item	Desc.	Material	Remark

△	2022/11/02	First edition release	Carl Hu	
SIDE	DATE	DESCRIPTION	APPROVER	
8	7	6	5	4

QUALITY SYMBOLS		Tolerance		NAME:	
□:	☒:	x.	±0.60	Centronics(57) 14pin female solder, flat shell	
CRITICAL	MAJOR	.x	±0.40	REV:	A
▽:	▽:	.xx	±0.25	SCALE:	N:1
ZERO DEFECT	S.P.C			UNIT:	mm
				DRW BY	Huangmei

PART NO.	B17-0144X1A0-M6	
CHK BY	APP BY	DRAWING NO.
Carl Hu		B17-062
东莞市林诚塑胶电子有限公司		
<a href="http://www.lineconn.com">http://www.lineconn.com</a> TEL: 0769-85181660 85181770		
3	2	1