



Current rating: 5A
 Withstanding voltage: 500V AC
 Insulation resistance: >1000 m Ω /Min
 Contact resistance: 30m Ω /Max
 Operation temperature: -55°C~+125°C
 ROHS compliant
 Part number:

B17-0504X1A0-M6

Housing color: _____
 1: Black
 6: Blue

3	Housing	PBT+G.F.30%	Color: see part number
2	Shell	SPCC	Plating: Ni
1	Terminal	Phosphor copper	Contact area: G/F Solder area: Sn Under-plating: Ni
Item	Desc.	Material	Remark

△	2022/11/07	First edition release	Carl Hu
SIDE	DATE	DESCRIPTION	APPROVER
8	7	6	5

QUALITY SYMBOLS		Tolerance	
□ :	☒ :	.x	±0.60
CRITICAL	MAJOR	.x	±0.40
▽ :	▽ :	.xx	±0.25
ZERO DEFECT	S.P.C		

NAME:	Centronics(57) 50pin female solder, flat shell			PART NO.	B17-0504X1A0-M6		
REV:	A	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.
SCALE:	N:1	DATE:	2022/11/07	Huangmei	Carl Hu		B17-064
				东莞市林诚塑胶电子有限公司			
				http://www.lineconn.com TEL:0769-85181660 85181770			
3	2					1	