



B-B

Voltage current rating: 0.5A
 Dielectric withstanding voltage: 500V
 Insulation resistance: 500MΩ Min.
 Temperature range: -45°C to +125°C

| | | | |
|------|----------|---------------|---|
| 4 | Shell | SPCC | Plated: Ni |
| 3 | Housing | LCP, UL 94-V0 | Color: black |
| 2 | Cover | LCP, UL 94-V0 | Color: black |
| 1 | Terminal | Copper alloy | Contact area: G/F Solder area: Sn Under-plating: Ni |
| Item | Desc. | Material | Remarks |

| | | | | | | | | | | | | | |
|------|------------|-----------------------|----------|----------------------|--------------|------------------------|-------------------------------------|-------|--|----------|-----------------|--------|-------------|
| △ | | | | QUALITY SYMBOLS | Tolerance | NAME: | VHDCI pitch 0.8mm 68pin male solder | | | PART NO. | B06-068311A0-03 | | |
| △ | | | | □: ☒: | .x ±0.60 | REV: | A | UNIT: | mm | DRW BY | CHK BY | APP BY | DRAWING NO. |
| △ | 2025/01/10 | First edition release | Carl Hu | CRITICAL MAJOR | .x ±0.40 | SCALE: | N:1 | DATE: | 2025/01/10 | Huangmei | Carl Hu | | B06-034 |
| SIDE | DATE | DESCRIPTION | APPROVER | ▽: ▽: | .xx ±0.25 | lineconn 东莞市林诚塑胶电子有限公司 | | | http://www.lineconn.com TEL: 0769-85181660 85181770 | | | | |
| 8 | 7 | 6 | 5 | ZERO DEFECT S.P.C | | 4 | 3 | 2 | 1 | | | | |

lineconn 东莞市林诚塑胶电子有限公司 <http://www.lineconn.com>
 TEL: 0769-85181660 85181770