


Pin assignment

P1	P2
01	01
02	02
03	03
04	04
05	05
06	06
07	07
08	08
09	09
Shell	Shell

Current rating: 3A
 Withstanding voltage: 500V AC
 Contact resistance : 35mΩ max.
 Insulation resistance: 500MΩ Min.
 Temperature range: -45℃ to +105℃
 Label: yellow color with black character
 ROHS compliant

Item	Desc.	Material	Remark
5	Screw	Steel	Plating: Ni
4	connecting	SPCC	Plating: Ni
3	Housing	PBT+G.F.30% (UL 94V-0)	Color: blue
2	Sheel	SPCC	Plating: Ni
1	Terminal	Copper alloy	Contact area: G/F Solder area: Sn Under-plating: Ni

SIDE	DATE	DESCRIPTION	APPROVER	QUALITY SYMBOLS	Tolerance	NAME:	MINI GENDER CHANGER D-SUB 9pin female to female adaptor	PART NO.	C05-009261AD-01				
△	2021/09/21	Change tolerance	Carl Hu	□: ☒:	x. ±0.60	REV:	C	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.
△	2021/06/04	Change part number	Carl Hu	CRITICAL MAJOR	.x ±0.40	SCALE:	N:1	DATE:	2014/08/18	Huangmei	Carl Hu		C05-015
△	2014/08/18	First edition release	Jack Chen	▽: ▽:	.xx ±0.25	 东莞市林诚塑胶电子有限公司			http://www.lineconn.com TEL:0769-85181660 85181770				
8	7	6	5	4	3	2	1						