



Pin assignment

P1	P2
01	01
02	02
03	03
04	04
05	05
06	06
07	07
08	08
09	09
10	10
11	11
12	12
13	13
14	14
15	15
Shell	Shell

Current rating: 3A  
 Dielectric strength: 1000V for one minute  
 Insulator resistance:  
 1000megohms min at 500V DC  
 Temperature: -45°C~105°C  
 Label: Yellow color with black character  
 ROHS compliant

Item	Desc.	Material	Remark
5	Screw	Steel	Plating: Ni
4	connecting	SPCC	Plating: Ni
3	Housing	PBT+G.F.30% (UL 94V-0)	Color: blue
2	Sheel	SPCC	Plating: Ni
1	Terminal	Copper alloy	Contact area: G/F Solder area: Sn Under-plating: Ni

△				QUALITY SYMBOLS	Tolerance	NAME:	MINI GENDER CHANGER D-SUB 15pin male to female adaptor			PART NO.	C05-015361AD-01		
△				□:    ☒:	.x    ±0.60	REV:	A	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.
△	2022/07/22	First edition release	Carl Hu	CRITICAL    MAJOR	.x    ±0.40	SCALE:	N:1	DATE:	2022/07/22	Huangmei	Carl Hu		C05-028
SIDE	DATE	DESCRIPTION	APPROVER	ZERO DEFECT    S.P.C	.xx    ±0.25								<a href="http://www.lineconn.com">http://www.lineconn.com</a> TEL:0769-85181660 85181770