

14	Nut	PA66	Color: brown
13	Clip	POM	Color: white
12	Sealing gasket	Rubber	Color: black
11	Cable sleeve	Zinc alloy	Plating: Ni
10	spring	Copper	Plating: Au
9	Terminals	Copper	Plating: Au
8	Terminals	Copper	Plating: Au
7	O-ring	rubber	Color: black
6	Housing	PPS	Color: black
5	Spring	Stainless spring steel	
4	gasket	Stainless spring steel	
3	Sealing ring	rubber	Color: black
2	Connection sleeve	Zinc alloy	Plating: Ni
1	Hood	Zinc alloy	Plating: Ni
Item	Desc.	Material	Remark


Current rating: 2 AMP.
 Operating voltage: 30V
 Contact resistance: 15mΩ/Max.
 Durability: 1000 cycles
 Temperature range: -25°C to +85°C
 ROHS compliant

QUALITY SYMBOLS

□: ☒: CRITICAL MAJOR
 ▽: ▽: ZERO DEFECT S.P.C

Tolerance

x. ±0.60
 .x ±0.40
 .xx ±0.25



NAME:	LF10WBP-12S female solder zinc alloy hood assembly			PART NO.	B10-0LF10WBP-12S		
REV:	A	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.
SCALE:	N:1	DATE:	2022/12/07	Huangmei	Jack Chen		B10-088

lineconn 东莞市林诚塑胶电子有限公司

http://www.lineconn.com
 TEL:0769-85181660 85181770

△	2022/12/07	First edition release	Jack Chen
---	------------	-----------------------	-----------

SIDE	DATE	DESCRIPTION	APPROVER
8	7	6	5

8 7 6 5 4 3 2 1