






Current rating: 2A
Rated voltage: 100V
Contact resistance: 10mΩ Max.
Durability: 1000 cycles
Temperature range: -25℃ to +85℃
ROHS compliant
Waterproof rating: IP67



7	Casing	Rubber	Color: black
6	Housing	PPS	Color: black
5	Spring	QBe1.9	
4	Terminal	Copper	Plating: Au
3	Cable sleeve	Copper	Plating: Ni
2	Connecting sleeve	Copper	Plating: Ni
1	Shell	Zinc alloy	Plating: Ni
Item	Desc.	Material	Remark

△	2023/03/09	First edition release	Carl Hu
SIDE	DATE	DESCRIPTION	APPROVER
8	7	6	5

QUALITY SYMBOLS		Tolerance	
□:	☒:	x.	±0.60
CRITICAL	MAJOR	.x	±0.40
▽:	▽:	.xx	±0.25
ZERO DEFECT	S.P.C		

NAME:		HR10A-7J-6P male solder assembly			PART NO.	B10-01PZ06SH-ZFD	
REV:	A	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.
SCALE:	N:1	DATE:	2023/03/09	Yugong	Carl Hu		B10-166
 东莞市林诚塑胶电子有限公司					http://www.lineconn.com TEL:0769-85181660 85181770		